

DOUBLE HUNG Features

	COLOR						GRIDS				GLASS TYPE			LOCKS			HANDLES			MULL TYPES		RETRO FIT and MISC ACC.						SCREENS		Installation Applications*		JAMB WIDTH		U Value	SHGC	Spacer	
	White (standard)	Adobe	Bronze/White Cwood SuperCap	White/Cherry	White/Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimaGuard Low E/Argon	Fuel Saver	Surface Mounted	Recessed	Fusion	Extruded	Applied	Routed	Snap-In (Factory or Jobsite)	T-Mull, Continuous head & sill (1)	Installation Screw Packs	Head Expander	Sill Expander	Night Latches	Jamb Foam	Balance Covers	Roll Formed	Extruded	Installation Applications *	Replacement	New Construction	Dual Glazed, Low E/Clear, Argon	Solar Heat Gain	Duraseal	Duralite
DOUBLE HUNG 4000	◆						W	W			*	◆		◆			◆			*	*	◆	*	◆	◆				◆		R, N, BJ, BF	3 ¼	2 ¼	.30	.29	◆	
4200	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	◆			◆			*	*	◆	◆	◆	◆	◆	◆		◆	R, N, BJ, BF	3 ¼	2 ¼	.30	.29	◆		
6400	◆	*	*	*		*	W,A, BR, CH,LT	W,A, BR, CH,LT	*	*		◆	*		◆	*		*	◆	*	*	◆	◆	◆	◆	◆	◆		◆	R, N, BJ	3 ¼	2 ¼	.28	.28		◆	
CompositWood® 9800/9900	◆		*			*	*	*	*	*		◆	*		◆					SEE BELOW			*		◆	◆	◆		◆	R	3 ¼		.25	.27		◆	

CompositWood Lift Rail Features

Bottom Sash			Top Sash		
Large Routed Rail	Large Flush Rail w/applied handle	Large Flush Rail (no handle)	Small Flush Rail w/applied handle	Small Flush Rail (no handle)	
◆	*	*	*	◆	

Double Hung Size Limits

4000 Series
W: 14½-48
H: 24-78
Max: 126 UI

6400 Series
W: 14½-48
H: 24-75
Max: 123 UI

9800 Series
W: 14½-53
H: 24-86
Max: 137 UI

9900 Series (Commercial)
W: 14½-57
H: 24-96
Max: 148 UI

(1) Max unit size:
T-Mull Continuous Head and Sill
W: 130
H: 78 (74" on 6400)

COLOR KEY: W=White, A=Adobe, BR=Bronze/White
CH=White/Cherry, LT=White/Lt Oak

INSTALLATION KEY: R = Replacement, N = Standard Nail Fin, BJ = Brickmold J-face Nail Fin, BF - Brickmold Only

For a complete list of options, see specific model number page.

◆ **Standard**

* **Optional**

SLIDER Features

	COLOR					GRIDS				GLASS TYPE			LOCKS		HANDLES		MULL TYPES	RETRO FIT and MISC ACC.					SCREENS		OPERATION		Install	JAMB WIDTH		U Value	SHGC	SPACER						
	White (standard)	Adobe	Bronze/White Cwood SuperCap	White/Cherry	White/ Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimateGuard Low E/Argon	Fuel Saver	Surface Mounted	Recessed	Fusion	Extruded	Applied	Routed	Snap-In (Factory or Jobsite)	T-Mull, Continuous Head & Sill	Installation Screw Packs	Head Expander	Sill Expander	Night Latches		Jamb Foam	Roll Formed			Extruded	Single Pocket	Dual Pocket	Dual Slide, Swing to Clean	Installation Applications *	Replacement	New Construction
SLIDER 4000 2 & 3 Lite	◆	* ⁽¹⁾				*	W,A, BR	W,A, BR			*	◆		◆			◆			*		◆	*	◆			◆					R, N, BJ, BF	3 ¼	2 ¼	.29	.31	◆	
4202 2 & 3 Lite	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	◆			◆	*		*		◆	◆	◆		◆					R, N, BJ, BF	3 ¼	2 ¼	.29	.28	◆		
6400 2 & 3 Lite	◆	*	*	*		*	W,A, BR, CH,LT	W,A, BR, CH,LT	*	*		◆	*	◆	*		*	◆	*	*		◆	◆	◆	◆	◆					R, N, BJ, BF	3 ¼	2 ¼	.28	.28		◆	
CompositWood®9800 2 & 3 Lite	◆		*			*		*	*	*		◆	*	◆			*	◆	*		◆					◆					R	3 ¼		.25	.28		◆	

◆ Standard

* Optional

COLOR KEY: W=White, A=Adobe, BR=Bronze/White
CH=White/Cherry, LT=White/Lt Oak

INSTALLATION KEY: R = Replacement, N = Standard Nail Fin,
BJ = Brickmold J-face Nail Fin, BF - Brickmold Only

For a complete list of options, see specific model number page.

(1) Optional color with slightly larger lift handle
(2) Bronze SuperCap exterior or painted exterior requires one sash of 2-lite slider to be fixed.

Slider Size Limits

Slider (2-Lite)

4000 Series Single Slider
W: 23-84
H: 14½-66
Max: 146 UI

4202 Series Dual Slider
W: 23-84
H: 14½-66
Max: 146 UI

9800 Series Dual Slider
W: 23-86
H: 14½-72
Max: 144 U

6400 Series Dual Slider
W: 24-78
H: 14½-60
Max: 120 UI

Slider (3-Lite)

4000 Series 2 operable sash, one fixed glass
W: 56-120
H: 14½-66
Max: 168 UI

4202 Series 2 operable sash, one fixed sash
W: 56-120
H: 14½-66
Max: 168 UI

9800 Series 2 operable sash, one fixed sash
W: 56-144
H: 14½-72
Max: 192 UI

6400 Series 2 operable sash, one fixed sash
W: 56-108
H: 14½-60
Max: 148 UI

CASEMENT & AWNING Features

	COLOR						GRIDS			GLASS TYPE		Hardware			MULL TYPES	RETRO FIT and MISC.			SCREENS		Install	JAMB WIDTH		U-Value	SHGC	SPACER						
	White (standard)	Adobe	Bronze/White Cwood SuperCap	White/Cherry	White/ Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimaGuard Low E/Argon	Fuel Saver		Multi Point, one handle operation	Slim Line Interior Latch	Folding Crank Handle	Stainless, multi point, 1 handle operation	Snap-In (factory or job site)		T-Mull, Continuous Head & Sill	Installation Screw Packs			Head Expander	Sill Expander	Jamb Foam	Roll Formed	Extruded	Installation Application *	Replacement
CASEMENT 4200	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	◆	◆	◆	*	*	*	◆				◆	R, N, BJ, BF	3 ¼	2 ¼	.27	.26	◆		
CASEMENT 6400	◆	*	*	*		*	W,A, BR, CH,LT	W,A, BR, CH,LT	*	*		◆	*	◆	◆	◆	*	*	*	◆				◆	R, N, BJ, BF	3 ¼	2 ¼	.25	.26		◆	
CompositWood® Casement 9800	◆		*			(1)	*	*	*	*		◆	*	◆	◆	◆	*	*		◆				◆	R	3¼		.23	.27		◆	
AWNING 4200	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	◆	◆	◆	*	*	*	◆				◆	R, N, BJ, BF	3 ¼	2 ¼	.27	.26	◆		
AWNING 6400	◆	*	*	*		*	W,A, BR, CH,LT	W,A, BR, CH,LT	*	*		◆	*	◆	◆	◆	*	*	*	◆				◆	R, N, BJ, BF	3 ¼	2 ¼	.26	.26		◆	
CompositWood® Awning 9800	◆		*			(1)	*	*	*	*		◆	*	◆	◆	◆	*	*		◆				◆	R	3¼		.23	.27		◆	

◆ **Standard** **COLOR KEY:** W=White, A=Adobe, BR=Bronze/White, CH=White/Cherry, LT=White/Lt Oak

* **Optional** **INSTALLATION KEY:** R = Replacement, N = Standard Nail Fin, BJ = Brickmold J-face Nail Fin, BF - Brickmold Only

(1) CompositWood casement/awning sash is white exterior and interior, with option for pine laminate interior sash. Frame interior receives real pine laminate.

Casement Size Limits

4200 Series
Operating Unit
W: 13¼-35¼
H: 20-76
Max: 108 UI

6400 Series
Operating Unit
W: 13¼-36
H: 20-80
Max: 116 UI

4200/6400 Series
Fixed Casment
W: 10-84
H: 10-84
Max: 156 UI

9800 Series

Operating Unit
W: 13¼-36
H: 20-80
Max: 116 UI
W: 13¼"- 16¼" open to 56 degrees, W: 17" and greater open to 90 degrees and can be cleaned from inside.

9800 Series

Fixed Casement
W: 12-84
H: 12-84
Max: 156 UI

Awning Size Limits

4200 Series

W: 14½-60
H: 13¼-36
Max: 96 UI
Only one dimension (W or H) can be less than 20 inches.
Heights 17¼" and under do not have sash locks.

6400 Series

W: 14½-60
H: 13¼-36
Max: 96 UI
Only one dimension (W or H) can be less than 20 inches.
Heights 17¼" and under do not have sash locks.

9800 Series

W: 16-60
H: 14-36
Max: 96 UI
Only one dimension (W or H) can be less than 20 inches.
Heights 18¼" and under do not have sash locks.

For a complete list of options, see specific model number page.

PATIO DOOR Features

	COLOR						GRIDS			GLASS TYPE		MULL TYPES		LOCKS			HANDLES		ROLLERS			SCREENS		Operation	SIGHT LINE	Install	JAMB WIDTH		U Value	SHGC	SPACER						
	White (standard)	Adobe	Bronze/White Cwood SuperCap	White/Cherry	White/ Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimaGuard Low E/Argon	Fuel Saver (1)	T-Mull	Snap-In (Factory or Jobsite)	Single Point	Multi Point	Key Lock	Foot Lock	Standard Handle	Deluxe Handle Set	Steel	Steel Precision Ball Bearing	Stainless Steel Precision Ball Bearing	Roll Formed Galvanized Steel with Latch	Extruded Aluminum with Consealed Auto Latch	Single panel, direct glaze panel, XO - OX	Dual Panel, XO - OX	Unequal Glass	Equal Glass	Installation Applications *	Replacement	New Construction	Dual glazed, Low E/Clear, Argon	Solar Heat Gain	Duraseal
PATIO DOOR 4000 (1)	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	*	*	◆		*	*	◆		◆	*	◆	*	◆				R, N, BJ	4 ½	3 ¼	.28	.33	(2)		
4202	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	*	*	◆		*	*	◆		◆	*	◆	*	◆			R, N, BJ	4 ¾	3 ½	.29	.32	(2)			
6400	◆	*	*	*		*	W,A, BR, CH,LT	W,A, BR, CH,LT	*	*	*	◆	*	*	*	◆	◆	◆	*	◆		◆	*	◆	*	◆			R, N, BJ	4 ¾	3 ½	.28	.32		(2)		
9400	◆		*		*	*	*	*	*	*	◆	*	*	*	*	◆	◆			◆		◆	*	◆	*	◆			*	4 9/16	##	##	.27	.30		(2)	

◆ Standard

* Optional

COLOR KEY: W=White, A=Adobe, BR=Bronze/White
CH=White/Cherry, LT=White/Lt Oak

INSTALLATION KEY: R = Replacement, N = Standard Nail Fin, BJ = Brickmold J-face Nail Fin. Brickmold J face shipped loose and field applied.

(1) Fuel Saver glass over 18 sq. ft. not available with Contour grids. Fuel Saver not available over 28 sq.ft. (3/16" and 1/4" glass)

(2) Endur Spacer in dual glazed; Duralite spacer in Fuel Saver

Patio Door Size Limits

2-Lite
4000/4202/6400/9400 Series
W: 50-96
H: 72-96
Max: 192 UI

3-Lite 4000 Series
W: 75-142½
H: 72-96
Max: 214 UI

4-Lite 4000 Series
W: 100-142½
H: 72-96
Max: 214 UI

3-Lite Series 4202/6400
W: 75-144
H: 72-96
Max: 240 UI

3-lite Series 9400
W: 75-145
H: 72-96
Max: 240 UI

4-Lite 4202/6400/9400 Series
W: 100-192
H: 72-96
Max: 288 UI

HOPPER Features

	COLOR					GRIDS			GLASS TYPE		LOCKS		HANDLES		MULL TYPES		RETRO FIT and MISC. ACCESSORIES			SCREENS		Install	JAMB WIDTH		U-Value	SHGC	SPACER							
	White (standard)	Adobe	White/Cherry	White/ Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimaGuard Low E/Argon	Fuel Saver	Surface Mounted	Recessed	Fusion	Extruded	Applied	Routed	Snap-In (Factory or Jobsite)	T-Mull, Continuous Head & Sill	Installation Screw Packs	Head Expander	Sill Expander	Dryer Vent Option	Jamb Foam	Roll Formed	Extruded	Installation Applications *	Replacement	New Construction	Dual glazed, Low E/Clear, Argon	Solar Heat Gain	Duraseal
HOPPER 4200	◆	*				*	W.A. BR	W.A. BR		*	◆	*	◆						*	*		*	◆	*				R, N, BJ, BF	3 ¼	2 ¼	.29	.27	◆	

SINGLE HUNG Features

	COLOR					GRIDS			GLASS TYPE		LOCKS		HANDLES		MULL TYPES		RETRO FIT and MISC. ACCESSORIES			SCREENS		Install	JAMB WIDTH		U-Value	SHGC	SPACER							
	White (standard)	Adobe	White/Cherry	White/ Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimaGuard Low E/Argon	Fuel Saver	Surface Mounted	Recessed	Fusion	Extruded	Applied	Routed	Snap-In (Factory or Jobsite)	T-Mull, Continuous Head & Sill	Installation Screw Packs	Head Expander	Sill Expander	Night Latches	Jamb Foam	Roll Formed	Extruded	Installation Applications *	Replacement	New Construction	Dual glazed, Low E/Clear, Argon	Solar Heat Gain	Duraseal
SINGLE HUNG 4000	◆	* (1)				*	W.A. BR	W.A. BR	*	*	◆		◆						*	*		*	◆					R, N, BJ, BF	3 ¼	2 ¼	.29	.31	◆	

- ◆ Standard
 - * Optional
- COLOR KEY:** W=White, A=Adobe, BR=Bronze/White
CH=White/Cherry, LT=White/Lt Oak
- INSTALLATION KEY:** R = Replacement, N = Standard Nail Fin,
BJ = Brickmold J-face Nail Fin, BF - Brickmold Only

BALANCES: All single hung windows feature Interstate's exclusive Light Lift™ Sash Balance System.

(1) Slightly larger lift handle

Hopper Size Limits
4200 Series
 W: 14-48
 H: 12-36
 Max: 81 UI

Hopper/Dryer Vent Combo
 4200 Series
 Size of Entire Unit including dryer vent:
 W: 25 1/8 - 96
 H: 12 3/4 - 36
 Dryer vent standard and minimum panel width is 11" regardless of window width. Custom panel widths over 11" optional. Glass size will vary depending on window width.
 Pipe Diameter: 4"
 Hole Size: 5 1/2" x 6 1/2"
 Vent Surface Dimension: 7" x 8"

Single Hung Size Limits
4000 Series
 W: 14 1/2-48
 H: 24-78
 Max: 126 UI

PICTURE WINDOW (Direct Set) Features

PICTURE	COLOR						GRIDS				GLASS TYPE			Mull Types		RETRO FIT and MISC ACC.				Install	JAMB WIDTH		U-Value	SHGC	SPACER	
	White (standard)	Adobe	Bronze/White Cwood SuperCap	White/Cherry	White/Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimaGuard Low E/Argon	Fuel Saver (1)	Snap-In (Factory or Jobsite)	T-Mull, Continuous Head & Sill	Installation Screw Packs	Head Expander	Sill Expander	Jamb Foam	Installation Application *	Replacement	New Construction	Dual glazed, Low E/Clear, Argon	Solar Heat Gain	Duraseal
Direct Set 4000	◆						W,A, BR	W,A, BR			*	◆		*	*	◆	◆	◆		R, N, BJ, BF	3 ¼	2 ¼	.26	.34	◆	
Direct Set 4200	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	*	*	◆	◆	◆	◆	R, N, BJ, BF	3 ¼	2 ¼	.26	.34	◆	
Direct Set 6400	◆	*		*	*	*	W,A, BR, CH,L	W,A, BR, CH,LT	*	*		◆	*	*	*	◆	◆	◆	◆	R, N, BJ, BF	3 ¼	2 ¼	.25	.33		◆
CompositWood® Direct Set 9800	◆		*			*	*	*	*	*		◆	*	*		◆			◆	R	3 ¼	3 ³ / ₁₆	.25	.35		◆

◆ Standard

* Optional

COLOR KEY: W=White, A=Adobe, BR=Bronze/White
CH=White/Cherry, LT=White/Lt Oak

INSTALLATION KEY: R = Replacement, N = Standard Nail Fin,
BJ = Brickmold J-face Nail Fin, BF - Brickmold Only

For a complete list of options, see specific model number page.

Picture Window Size Limits

4000 Series

W: 12-84
H: 12-84
Max: 156 UI

4200/6400 Series

W: 12-84
H: 12-84
Max: 156 UI

9800 Series

W: 12-120
H: 12-91
Max: 192 UI

**(1) Fuel Saver glass over 18 sq. ft. not available with Contour grids.
Fuel Saver not available over 28 sq.ft. (3/16" and 1/4" glass)**

PICTURE WINDOW with Sash Insert, Fixed Casement Picture Window Features

PICTURE	COLOR						GRIDS				GLASS TYPE		Mull Types		RETRO FIT and MISC ACC.			Install	JAMB WIDTH		U-Value	SHGC	SPACER			
	White (standard)	Adobe	Bronze/White Cwood SuperCap	White/Cherry	White/Lt Oak	White/Pine	Custom Color	Flat Colonial *	Contour Colonial *	Polished Brass	Simulated Divided Lites (SDLs)	Clear	ClimaGuard Low E/Argon	Fuel Saver (1)	Snap-In (Factory or Jobsite)	T-Mull, Continuous Head & Sill	Installation Screw Packs	Head Expander	Sill Expander	Jamb Foam	Installation Application *	Replacement	New Construction	Dual glazed, Low E/Clear, Argon	Solar Heat Gain	Duraseal
4000 Picture with Sash Insert (2)	◆						W,A, BR	W,A, BR			*	◆		*	*	◆	◆	◆		R, N, BJ, BF	3 ¼	2 ¼	.27	.30	◆	
4200 Picture with Sash Insert (3)	◆	*				*	W,A, BR	W,A, BR	*		*	◆	*	*	*	◆	◆	◆	◆	R, N, BJ, BF	3 ¼	2 ¼	.27	.30	◆	
6400 Picture with Sash Insert (4)	◆	*		*	*	*	W,A, BR, CH,LT	W,A, BR, CH,LT	*	*		◆	*	*	*	◆	◆	◆	◆	R, N, BJ, BF	3 ¼	2 ¼	.26	.30		◆
CompositWood® 9800 Picture with Sash Insert	◆		*			*	*	*	*	*		◆	*	*	*	◆	*	◆	◆	R	3 ¼		.24	.28		◆
4200 Fixed Casement Picture Window	◆	*				*	W,A, BR	W,A, BR	*		◆	*	*	*	*	◆	*	◆	◆	R, N, BJ, BF	3 ¼	2 ¼	.26	.30	◆	
6400 Fixed Casement Picture Window	◆	*		*	*	*	W,A, BR, CH,LT	W,A, BR, CH,LT	*	*		◆	*	*	*	◆	*	◆	◆	R, N, BJ, BF	3 ¼	2 ¼	.25	.30		◆
CompositWood® 9800 Fixed Casement Picture Window	◆		*			(5)	*	*	*	*		◆	*	*	*	◆	*	N/A		R	3 ¼		.23	.27		◆

◆ Standard

* Optional

COLOR KEY: W=White, A=Adobe, BR=Bronze/White
CH=White/Cherry, LT=White/Lt Oak

INSTALLATION KEY: R = Replacement, N = Standard Nail Fin,
BJ = Brickmold J-face Nail Fin, BF - Brickmold Only

For a complete list of options, see specific model number page.

(1) Fuel Saver glass over 18 sq. ft. not available with Contour grids.
Fuel Saver not available over 28 sq.ft. (3/16" and 1/4" glass)

(2) Only for use in combination with model 4000 Double Hung with
continuous head and sill. Not available as stand alone picture window.

(3) Only for use in combination with model 4200 Double Hung with
continuous head and sill. Not available as stand alone picture window.

(4) For use in combination with model 6400 Double Hungs and
Picture Windows with continuous head and sill, as a stand-
alone picture window, or snap-in mull to any 6400 window style.

Picture Window with Sash Insert Size Limits

4000/4200 Series	6400Series	CompositWood®
W: 14¼-78	W: 14¼-84	9800 Series
H: 13¼-78	H: 13¼-84	W: 12-84
Max: 142 UI	Max: 156 UI	H: 14-84
		Max: 156 UI

Fixed Casement Picture Window Size Limits

4200/6400 Series	CompositWood 9800 Series
W: 10-84	W: 12-84
H: 10-84	H: 12-84
Max: 156 UI	Max: 156 UI

(5) CompositWood casement/awning sash is white exterior and interior, with option for pine laminate interior sash. Frame interior receives real pine laminate.